

EXTERIOR FINISH
AS SPEC'D

2x SILL C/W ANCHOR
BOLT, AS SPEC'D

ELEMENT TAPER TOP

ICF WALL REINF.
SEE NOTES

ELEMENT
HEIGHT ADJUSTER

ELEMENT ICF
(6" SHOWN)

PARGING, AS SPEC'D

BACKFILL
(FREE DRAINING)

WATERPROOFING

FILTER FABRIC
(OPTIONAL)

3/4" CRUSHED STONE

4" PERF. DRAIN TILE

40 x BAR DIAM

4" CONC. SLAB

UNDERSLAB
INSULATION

FTG, AS SPEC'D

8'-0"
6 COURSES + HEIGHT ADJUSTER = 8'-4"

NOTES:

1. Refer to the Element Prescriptive Engineering for reinforcement design of Element ICF walls.
2. Bottom course of Element is shown with the bottom interlocks removed. Optionally, leaving interlocks in place will increase wall or footing height by 0.525"



©Copyright Logix Brands Ltd. (2024) All rights reserved. No part of the work contained herein as covered by this copyright may be reproduced or used in any form, or any means - graphic, electronic or mechanical, including without limitation photocopying.

By using these drawings, you agree to assume all risks associated therewith. See Logixbrands.com/Disclaimer-Drawings for a full copy of disclaimer.

Drawing:
5.5.3.2

Date:
Mar 03/23

Pg:
1/1

Title:
8'-4" FOUNDATION WITH ELEMENT
TAPER TOP & HEIGHT ADJUSTER