

V•ROD POLY 46

GLASS FIBER REINFORCED POLYMER (GFRP) REBAR

REVISION: February, 2025

Product Data Sheet - V•ROD POLY 46

		#2	#3	#4	#5
Minimum tensile strength (ASTM D7205)	ksi	145			
Minimum V•ROD tensile load capacity	lbf	7 105	15 950	29 000	44 950
Average steel tensile load capacity	lbf	3 300	7 300	13 000	20 200
Minimum tensile modulus	ksi	6 800			
Weight	lb/ft	0.043	0.099	0,171	0,27
Measured diameter	in	0.289	0.398	0.512	0.634
Nominal cross-sectional area*	in ²	0.049	0.11	0.2	0.31



4x Lighter
Than Steel



2,5 x Stronger
Than Steel



Resilient



Durability /
Corrosion
Resistance



Radio /cellular
waves permeable

Only 2 lbs
per 20' stick!

V•ROD
USA

This data sheet is for V-ROD46, but the drawings are indicating V-ROD40.

440 Blackhawk Park Ave, Rockford, IL 61104, United States

sales@fiberglassrebar.com

Phone: 815-962-9338 | www.fiberglassrebar.com

RAISING THE BAR



**V-ROD
POLY**
ICC-ES CERTIFIED PRODUCT

V-ROD Poly fiberglass rebar offers many advantages:

- 4 times lighter than steel means; easier to install, less placement time and reduced transportation cost.
- 4 times lighter also means reduced physical burden on workers, less injuries and reduced down time.
- V-ROD is resilient; Unlike steel, when stepped/driven on, V-ROD will deform and get back to its original shape
- V-ROD's sand coating and higher tensile strength provides with the best crack control among any kind of rebar available on the market.
- V-ROD does not rust! No more cracks due to corrosion.
- Bar certs to be provided on every lot
- Radio/cellular waves permeable

V-ROD is well suited for:

Slab on grade, Basement, Garage, Foundations, Commercial Slabs, Sidewalk...



It should be noted that these drawings are for reference only and depend on the project requirements. The same reinforcement is shown for V-ROD40 and V-ROD46.

Basement slabs	Garage slabs	Foundation walls	Commercial slabs
• V-ROD Poly	• V-ROD Poly for light vehicles (not exceeding 4 tons) • Engineering required for heavy loads	• V-ROD Poly for horizontal • Engineering required for heavy loads	• V-ROD Poly for light loads (less than 100 PSF for instance) • Engineering required for heavy loads